



SEA OLOUS

TECHNICAL SPECIFICATIONS

GENERAL

Type	EuroCarrier 2611
Classification	Bureau Veritas • Hull • Mach • / Unrestricted
	Navigation / AUT-UMS ULEV
MMSI	246808000
IMO number	9997488
Year built	2023 - Neptune Hardinxveld, NL
Flag	Dutch
Port of registry	Vlissingen
Call sign	PFVV

DIMENSIONS

Length	26,48 m
Breadth overall	11,00 m
Minimum draft	2,50 m
Operational Draft	2,60 m
Maximum draft	3,25 m
Minimum air draft	9,00 m
Maximum air draft	17,50 m
Gross tonnage	255 t
Net tonnage	76 t

TANK CAPACITY

Fuel oil	110,0 + Urea 8 m ³
Fresh water	39,0 m ³
Lubrication oil	1,6 m ³
Hydraulic oil	1,6 m ³
Dirty oil	1,6 m ³
Sewage	7,0 m ³
Bilge water	9,0 m ³

PERFORMANCE

BollardPull	35 t
Maximum speed	10,00 knots
Economic speed	8,00 knots
Horse power	1940 kW

PROPULSION SYSTEM

Main engines	2x Caterpillar C32 Tier III
Total power	2x 970kW @ 1800 RPM
Propulsion	2x fixed propellor - 1850mm dia in nozzle
Bowthruster	250kW, tunnel thruster in SB pushbow

DECK CRANE

Type	AFT: Heila HLRM 140-3S / FWD: Heila HLRM 230-4SLK
Capacity	AFT: 26t @ 5.65m / FWD: 24.4t @ 7.89m

DECK EQUIPMENT

Free deckspace	145 m ²
Deck strength	6t/m ²
Tugger winch	Tecnospirit 15t / 22.5t (pull/hold) 150 m x 28 mm
Pushbow	double push bow - fully fendered

AUXILIARY EQUIPMENT

Main generator sets	2x Volvo D8 MG Tier III - 278kVa - 50Hz + CAT C4.4
Fuel oil transfer pump	100m ³ /hr @ 5.2 bar
Fresh water transfer pump	80m ³ /h @ 2.1 bar
Air compressor	Atlas copco 7.14kW
Powerpack	2x 90kW - electric hydraulic

ACCOMMODATION

Persons	6
Single cabin	6
Air conditioned	Yes

TOWING EN ANCHOR HANDLING

Towing winch	Tecnospirit 50t / 60t (pull/hold) 500 m x 36 mm
Anchor Handling Winch	Tecnospirit 100t / 150t (pull/hold) 350 m x 52 mm
Towing pins	SWL 50t + chain stopper 95t
Stern roller	dia 838mm, length 5m / BOW Roller: dia 1207mm, 6 m



SEACONTRACTORS

SEACONTRACTORS | VISSERIJKADE 95 | 4382 ZA VLISSINGEN | THE NETHERLANDS | T: +31 (0) 118 410 520 | WWW.SEACONTRACTORS.COM | INFO@SEACONTRACTORS.COM

The information contained in this data sheet is for guidance purposes only and may be subject to changes